2400 WSE/1 230

Angle grinder
2400 WSE/1 230

+ 2.400 watt high-performance motor
+ Starting current limitation for user-friendly start-up
+ Armoured motor winding to protect against dust and particles

Order number: 06046503

Technical Data

Nominal rated input	2.400	Watt
No-load speed	6.500	1/min.
Diameter of grinding disk	230	mm
Spindle thread	M 14	
Disk holder bore	22,2	mm
Tool weight	6,0	kg

Product features

+ Safety switch for high level of safety and working comfort
+ Spindle lock for quick grinding disk change
+ Carbon cut-off brush for motor protection
+ Aluminium die-cast gear casing
+ Service cover for carbon brush change
+ 4 m rubber mains cable

Scope of delivery

Additional handle, face spanner (no cut-off disk)

Available as accessory

Separating shield cover 230-1 (Product no. 98 04 2002)

Noise/Vibration Information

vibration emission level a_h	3.5	m/s^2
uncertainty velue K	1.5	m/s^2
sound pressure level L_{pA}	92	dB(A)
uncertainty velue K	3.0	dB(A)
noise power level L_{wA}	103	dB(A)
uncertainty velue K	3.0	dB(A)

L_{pA} = A-rated sound pressure level, L_{wA} = A-rated sound power level
K = Measurement uncertainty value, a_h = Triaxial vibration emission level

Measurement values determined according to **EN 60745.**

Further noise and vibration information

KRESS-elektrik GmbH & Co. KG | P.O.Box 166, 72403 Bisingen, Germany
Phone +49 (0) 7476 / 87-300 | Fax +49 (0) 7476 / 87-191 | E-mail: **info@kress-elektrik.de** | **www.kress-elektrik.com**